

## **SCAiLX Accelerator**

SCAILX-ACC26

## **Product Features**

- Up to 26 TOPS (Tera Operations per Second)
- Powered by Hailo-8
- Supports: TensorFlow, TensorFlow Lite, Keras, PyTorch & ONNX



## **Technical Specifications**

**Processing** 

Processor	Hailo-8
Compute Power	Up to 26 TOPS
Operating System (OS)	Linux
Al Framework	TensorFlow, TensorFlow Lite, Keras, PyTorch & ONNX
Conductivity	PCle Gen3, 1-lane

### Mechanical


Dimensions (WxHxD)	42 mm x 42 mm x 8.6 mm (1.65 " x 1.65 " x 0.34 ")
Weight	12 g (0.42 oz)


#### **Electrical**

Power Supply	3V3 Internally (max. 3 A)
Power Consumption	2.5 W Typical (8.25 W Max.)

#### **Environmental**

Operating Temperature	-20° C ~ 60° C (-4° F ~ 140° F)
Storage Temperature	-40° C ~ 85° C (-40° F ~ 185° F)







# www.videologyinc.com

#### **HEADQUARTERS LOCATION**

Videology Industrial-Grade Cameras 35 Hampden Road Mansfield | MA 02048 United States

#### **EUROPE LOCATION**

Videology Industrial-Grade Cameras High Tech Campus 5 5656 AE Eindhoven | The Netherlands

